




6024 Step ladder, double-sided accessible

- › Stable concept of D-shaped stiles for considerably higher feeling of safety when working on the step ladder and 4-times higher torsional stability of the stiles.
- › Step depth 80 mm.
- › Two high-strength restraining straps as safety strut.
- › Maintenance-free hinge components (dirt cannot accumulate).



Number of steps		2×2*	2×3	2×4	2×5	2×6	2×7	2×8	2×10
Stile	approx. mm	81	81	81	81	81	81	81	81
Length	approx. m	0.52	0.78	1.02	1.26	1.50	1.77	2.00	2.50
Standing height	approx. m	0.21	0.21	0.44	0.67	0.91	1.14	1.37	1.83
Working height	approx. m	1.71	1.71	1.94	2.17	2.41	2.64	2.87	3.33
Reach height	approx. m	2.21	2.21	2.44	2.67	2.91	3.14	3.37	3.83
Total vertical height	approx. m	0.45	0.65	0.90	1.15	1.35	1.60	1.80	2.30
Width top/bottom	approx. mm	375/425	375/450	375/475	375/500	375/525	375/550	375/575	375/625
Base width	approx. m	0.55	0.75	0.95	1.15	1.35	1.55	1.75	2.10
Weight	approx. kg	3.2	4.6	5.7	6.9	8.1	9.5	10.8	13.7
EAN-Code		4019502339620	4019502339637	4019502339644	4019502339651	4019502339668	4019502339675	4019502339682	4019502339699
Order no.		602404	602406	602408	602410	602412	602414	602416	602420

* The size 2×2 cannot be used according to DIN EN 131 and may only be accessed on the bottom-most step.
Therefore make sure that sufficient safety is provided (e. g. by holding to a fixed point).

For an explanation of working/standing/reach height see on page 5.

Recommended accessory:



P. 181

Retaining bracket

› Order no. 0051483