

STANDARD FIBREGLASS LADDERS

FIBREGLASS TWO SECTION COMBINATION LADDER

Can be used as a double-sided ladder and as a push-up extension ladder.
The two sections can be separated.

Standard
UNE-EN 131Standard
UNE-EN 50528Insulation
100 KV

Ref.	N° Rungs				Kg
FC6206	2x6	1780	3000	665	15
FC6207	2x7	2060	3560	705	16.5
FC6208	2x8	2340	4120	745	18
FC6209	2x9	2660	4680	795	19.5
FC7210	2x10	2940	4960	835	21
FC7211	2x11	3220	5520	880	22.5
FC7212	2x12	3500	6080	925	24



Ref. FC7210

FIBREGLASS THREE SECTION COMBINATION LADDER

Can be used as a double-sided ladder and as a push-up extension ladder.
The two sections can be separated.

Standard
UNE-EN 131Standard
UNE-EN 50528Insulation
100 KV

Ref.	N° Rungs				Kg
FC7306	3x6	1885	2985	4115	25
FC7307	3x7	2165	3545	4955	27
FC7308	3x8	2445	4105	5795	29
FC7309	3x9	2725	4385	6075	31
FC7310	3x10	3005	4945	6915	33
FC7311	3x11	3285	5505	7755	35



Ref. FC7310