

7075




ADVANCED SAFE-T mobile tower with stabiliser

**Maximum safety, convincingly comfortable:**

Secure standing space in every phase of assembly thanks to SAFE-T safety guardrail, already hooked in from below. Telescopic stabiliser with bayonet catch at a reach height of 9.27 metres to compensate for uneven ground. Weatherproof and non-slip large-area platform. With four height-adjustable swivel castors.

Features:

- **Work platform: 2.08 x 0.61 m**
- **Castors: Ø 150 mm**
- **Permissible load: 200 kg/m² (2.0 kN/m²)**

							
Assembly configurations	Module 1	Module 1+KIT +stabiliser	Module 1+2	Module 1+2+KIT	Module 1+2+3	Module 1+2+3+KIT	Module 1+2+3+4
Reach height (approx. m)	3.27	4.27	5.27	6.27	7.27	8.27	9.27
Tower height (approx. m)	2.49	3.49	4.49	5.49	6.49	7.49	8.49
Standing height (approx. m)	1.27	2.27	3.27	4.27	5.27	6.27	7.27
Platform length (approx. m)	2.08	2.08	2.08	2.08	2.08	2.08	2.08
Frame section width (approx. m)	0.72	0.72	0.72	0.72	0.72	0.72	0.72
Ballasting							
Indoor, centre (kg)	80	0	0	0	40 ⁽³⁾	100/40 ⁽⁴⁾	220
Indoor, on wall (kg)	80 ⁽¹⁾	50 ⁽¹⁾	80 ⁽¹⁾	120 ⁽¹⁾	150 ⁽¹⁾	190 ⁽¹⁾	190 ⁽¹⁾
Outdoor, centre (kg)	140	0	0	0	40 ⁽³⁾	120/60 ⁽⁴⁾	240
Outdoor, on the wall (kg)	140 ⁽¹⁾	70 ⁽¹⁾	110 ⁽¹⁾	160 ⁽¹⁾	220 ⁽¹⁾	290 ⁽¹⁾	0 ⁽²⁾
Order no.	707503	707504	707505	707506	707507	707508	707509

⁽¹⁾ Ballasting is not required when two wall connectors (707241) are used.

⁽²⁾ Two wall connectors (707241) need to be used.

⁽³⁾ Ballasting is not required when using four stabiliser extensions (707037).

⁽⁴⁾ When using four stabiliser extensions (707037).

Required additional parts from page 23.

Individual parts and parts list can be found in the instructions for assembly and use on page 3. | [Click here.](#)